

THERMOBOX[®] C210 – ACTIVE COOLING

hofland

GROOTKEUKEN &
CATERING EQUIPMENT



GUIDES	OUTER	INNER	WEIGHT	TECHNICAL SPECIFICATIONS
<p>14 x GN 1/1 80mm spacing</p>	<p>W: 525mm D: 825mm H: 1515mm</p>	<p>W: 330mm D: 540mm H: 1160mm</p>	<p>75 kg</p>	<p>Exterior walls: ABS plastic. Inner container: Welded container in stainless steel. Guides: Stainless steel, pressed from the inner container. Insulation: Polyurethane foam. Door: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic. Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two braked and two fixed. Top frame: Stainless steel and PVC corners. Trolley frame: Reject list of galvanized steel coated with PVC. C: Efficient compact chillers with electronic temperature control AA120, 27V DC. 230V/245W AC, insulation class IP44.</p>
<p>Product number: 122209-ZC SDX Thermobox C210 (14 GN 1/1) Single handed grip handle <i>Additional pull handles on the sides, at the back, are included</i></p> <p>Product number: 122209-XC SDX Thermobox C210 (14 GN 1/1) Excenter lock <i>Additional pull handles on the sides, at the back, are included</i></p>				