

hofland

GROOTKEUKEN &
CATERING EQUIPMENT



GUIDES	OUTER	INNER K	INNER F	WEIGHT	TECHNICAL SPECIFICATIONS
6+6 x GN 1/1 80mm spacing	W: 525mm D: 750mm H: 1665mm	W: 330mm D: 540mm H:510mm	W: 330mm D: 540mm H:510mm	124 kg	<p>Exterior walls: ABS plastic. Inner container: Welded container in stainless steel. Guides: Stainless steel, pressed from the inner container. Insulation: Polyurethane foam. Door: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic. Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two braked and two fixed. Top frame: Stainless steel and PVC corners. Trolley frame: Reject list of galvanized steel coated with PVC. K: Efficient convection cooling with electronic temperature control 230V/190W, insulation class IP44. F: Efficient convection heating system, with electronic temperature control, insulation class IP 44, 230V/550W. CE and S mark.</p>
<p>230V/190W AC + 230V/550W Product number: 122215-ZKF SDX Thermobox KF180 ECO (6+6 GN 1/1) Single handed grip handle</p> <p>230V/190W AC + 230V/550W Product number: 122215-XKF SDX Thermobox KF180 ECO (6+6 GN 1/1) Eccentric lock</p>					